

09/970,453
updated Search
2/11/07

d his

(FILE 'HOME' ENTERED AT 17:00:52 ON 09 FEB 2007)

FILE 'BIOSIS, CAPLUS, EMBASE, MEDLINE, JAPIO' ENTERED AT 17:01:36 ON 09
FEB 2007

L1 16100 S MICROFLUID?
L2 892 S L1 AND VELOC?
L3 310 S L2 AND TIME?
L4 1 S L2 AND PLURALI?
L5 8 S L3 AND PD<2000

=>

AN 1999:438989 CAPLUS

DN 131:85047

ED Entered STN: 16 Jul 1999

TI Whole blood diagnostics in standard gravity and microgravity by use of microfluidic structures (T-sensors)

AU Weigl, Bernhard H.; Kriebel, Jennah; Mayes, Kelly J.; Bui, Todd; Yager, Paul

CS Department Bioengineering, Univ. Washington, Seattle, WA, 98195, USA

SO Mikrochimica Acta (1999), 131(1-2), 75-83

CODEN: MIACAQ; ISSN: 0026-3672

PB Springer-Verlag Wien

DT Journal

LA English

CC 9-5 (Biochemical Methods)

AB In channels with dimensions much less than 1 mm, fluids with viscosities similar to or higher than that of water and flowing at low velocities exhibit laminar behavior. This allows the adjacent flow of fluids and particles in a channel without mixing other than by diffusion. The authors demonstrate the use of a 3-input microfluidic device known as a T-Sensor for the anal. of blood. A sample solution (e.g. whole blood), a receptor solution (e.g. an indicator solution), and a reference solution (a known analyte standard) are introduced into a

common channel (T-Sensor), and flow side by side until they leave the structure. Smaller particles such as ions or small proteins diffuse rapidly across the fluid boundaries, whereas larger mols. diffuse more slowly. Large particles (e.g. blood cells) show no significant diffusion within the time the flow streams are in contact. 2 Interface zones are formed between the fluid layers. The ratio of a property (e.g. fluorescence intensity) of the outer portions of the 2 interface zones is a function of the concentration of the analyte, and is largely free of cross-sensitivities to other sample components and instrument parameters. This device allows, for example, one-time or continuous monitoring of the concentration of analytes in microliters of whole blood

without

the use of membranes or prior removal of blood cells. The principle is illustrated by the determination of pH and human albumin in whole blood and serum.

Results are also presented for 0-gravity expts. performed with a T-Sensor on board a NASA exptl. plane. Due to its microfluidic flow characteristics, a T-Sensor functions independently of orientation and strength of the gravitational field. This was demonstrated by exposing a T-Sensor to variations in gravity from 0-1.8 g in a NASA KC135A plane flying repetitive parabolic flight curves.

ST blood analysis pH gravity microgravity microfluidity T sensor;
biosensor blood analysis pH microfluidity gravity microgravity;
microanalysis blood pH gravity microgravity microfluidity

IT Microanalysis

Space travel

Viscosity

pH

(laminar flow of whole blood in standard gravity and microgravity studied by microfluidic structures)

IT Flow

(laminar; Laminar flow of whole blood in standard gravity and microgravity studied by microfluidic structures (T-sensors))

IT Fluidization

(microfluidization; whole blood diagnostics in standard gravity and microgravity by microfluidic structures (T-sensors))

IT Biosensors

Blood analysis

Gravity

Microgravity

AN 1999:438989 CAPLUS

DN 131:85047

ED Entered STN: 16 Jul 1999

TI Whole blood diagnostics in standard gravity and microgravity by use of microfluidic structures (T-sensors)

AU Weigl, Bernhard H.; Kriebel, Jennah; Mayes, Kelly J.; Bui, Todd; Yager, Paul

CS Department Bioengineering, Univ. Washington, Seattle, WA, 98195, USA

SO Mikromedica Acta (1999), 131(1-2), 75-83

CODEN: MIACAQ; ISSN: 0026-3672

PB Springer-Verlag Wien

DT Journal

LA English

CC 9-5 (Biochemical Methods)

AB In channels with dimensions much less than 1 mm, fluids with viscosities similar to or higher than that of water and flowing at low velocities exhibit laminar behavior. This allows the adjacent flow of fluids and particles in a channel without mixing other than by diffusion. The authors demonstrate the use of a 3-input microfluidic device known as a T-Sensor for the anal. of blood. A sample solution (e.g. whole blood), a receptor solution (e.g. an indicator solution), and a reference solution (a known analyte standard) are introduced

into a common channel (T-Sensor), and flow side by side until they leave the structure. Smaller particles such as ions or small proteins diffuse rapidly across the fluid boundaries, whereas larger mols. diffuse more slowly. Large particles (e.g. blood cells) show no significant diffusion within the time the flow streams are in contact. 2 Interface zones are formed between the fluid layers. The ratio of a property (e.g. fluorescence intensity) of the outer portions of the 2 interface zones is a function of the concentration of the analyte, and is largely free of cross-sensitivities to other sample components and instrument parameters. This device allows, for example, one-time or continuous monitoring of the concentration of analytes in microliters of whole blood

without the use of membranes or prior removal of blood cells. The principle is illustrated by the determination of pH and human albumin in whole blood and serum.

Results are also presented for 0-gravity expts. performed with a T-Sensor on board a NASA exptl. plane. Due to its microfluidic flow characteristics, a T-Sensor functions independently of orientation and strength of the gravitational field. This was demonstrated by exposing a T-Sensor to variations in gravity from 0-1.8 g in a NASA KC135A plane flying repetitive parabolic flight curves.

ST blood analysis pH gravity microgravity microfluidity T sensor;
biosensor blood analysis pH microfluidity gravity microgravity;
microanalysis blood pH gravity microgravity microfluidity

IT Microanalysis

Space travel

Viscosity

pH

(laminar flow of whole blood in standard gravity and microgravity studied by microfluidic structures)

IT Flow

(laminar; Laminar flow of whole blood in standard gravity and microgravity studied by microfluidic structures (T-sensors))

IT Fluidization

(microfluidization; whole blood diagnostics in standard gravity and microgravity by microfluidic structures (T-sensors))

IT Biosensors

Blood analysis

Gravity

Microgravity

(whole blood diagnostics in standard gravity and microgravity by
microfluidic structures (T-sensors))

RE.CNT 15 THERE ARE 15 CITED REFERENCES AVAILABLE FOR THIS RECORD
RE

- (1) Afromowitz, M; Sep Sci Tech 1989, V24, P325 CAPLUS
- (2) Brody, J; Low Reynolds Number Micro-Fluidic Devices, Solid-State Sensor and Actuator Workshop 1996
- (3) Cefai, J; J Micromech Microeng 1994, V4, P172 CAPLUS
- (4) Cussler, E; Diffusion, Mass Transfer in Fluid Systems 1984, P525
- (5) Einstein, A; Investigations on the Theory of the Brownian Movement 1956, P122
- (6) Elwenspoek, M; J Micromech Microeng 1994, V4, P227 CAPLUS
- (7) Galambos, P; Transducers 97 (International Conference of Solid-State, Sensors and Actuators) 1997, V1, P535 CAPLUS
- (8) Gravesen, P; J Micromech Microeng 1993, V3, P168 CAPLUS
- (9) Happel, J; Low Reynolds Number Hydrodynamics, 2nd Ed 1973, P553
- (10) Harrison, D; Science 1993, V261, P895 CAPLUS
- (11) Manz, A; J High Res Chromatogr 1993, V16, P433 CAPLUS
- (12) Weigl, B; Anal Meth Instrum 1996
- (13) Weigl, B; Sens Actuators B 1997, V39, P452
- (14) Yager, P; US 5716852 1998 CAPLUS
- (15) Zengerle, R; J Micromech Microeng 1994, V4, P192 CAPLUS

(whole blood diagnostics in standard gravity and microgravity by
microfluidic structures (T-sensors))

RE.CNT 15 THERE ARE 15 CITED REFERENCES AVAILABLE FOR THIS RECORD
RE

- (1) Afromowitz, M; Sep Sci Tech 1989, V24, P325 CAPLUS
- (2) Brody, J; Low Reynolds Number Micro-Fluidic Devices, Solid-State Sensor and Actuator Workshop 1996
- (3) Cefai, J; J Micromech Microeng 1994, V4, P172 CAPLUS
- (4) Cussler, E; Diffusion, Mass Transfer in Fluid Systems 1984, P525
- (5) Einstein, A; Investigations on the Theory of the Brownian Movement 1956, P122
- (6) Elwenspoek, M; J Micromech Microeng 1994, V4, P227 CAPLUS
- (7) Galambos, P; Transducers 97 (International Conference of Solid-State, Sensors and Actuators) 1997, V1, P535 CAPLUS
- (8) Gravesen, P; J Micromech Microeng 1993, V3, P168 CAPLUS
- (9) Happel, J; Low Reynolds Number Hydrodynamics, 2nd Ed 1973, P553
- (10) Harrison, D; Science 1993, V261, P895 CAPLUS
- (11) Manz, A; J High Res Chromatogr 1993, V16, P433 CAPLUS
- (12) Weigl, B; Anal Meth Instrum 1996
- (13) Weigl, B; Sens Actuators B 1997, V39, P452
- (14) Yager, P; US 5716852 1998 CAPLUS
- (15) Zengerle, R; J Micromech Microeng 1994, V4, P192 CAPLUS

ANSWER 1 OF 8 BIOSIS COPYRIGHT (c) 2007 The Thomson Corporation on STN

AN 1997:341070 BIOSIS

DN PREV199799640273

TI A novel instrument for studying the flow behaviour of erythrocytes through microchannels simulating human blood capillaries.

AU Sutton, N. [Reprint author]; Tracey, M. C.; Johnston, I. D.; Greenaway, R. S.; Rampling, M. W. [Reprint author]

CS Dep. Physiol. Biophys., Imperial Coll. Sch. Med., St. Mary's, London W2 1PG, UK

SO Microvascular Research, (1997) Vol. 53, No. 3, pp. 272-281.
CODEN: MIVRA6. ISSN: 0026-2862.

DT Article

LA English

ED Entered STN: 11 Aug 1997
Last Updated on STN: 11 Aug 1997

AB A novel instrument has been developed to study the microrheology of erythrocytes as they flow through channels of dimensions similar to human blood capillaries. The channels are produced in silicon substrates using microengineering technology. Accurately defined, physiological driving pressures and temperatures are employed whilst precise, real-time image processing allows individual cells to be monitored continuously during their transit. The instrument characterises each cell in a sample of ca. 1000 in terms of its volume and flow velocity profile during its transit through a channel. The unique representation of the data in volume/velocity space provides new insights into the microrheological behaviour of blood. The image processing and subsequent data analysis enable the system to reject anomalous events such as multiple cell transits, thereby ensuring integrity of the resulting data. By employing an array of microfluidic flow channels we can integrate a number of different but precise and highly reproducible channel sizes and geometries within one array, thereby allowing multiple, concurrent, isobaric measurements on one sample. As an illustration of the performance of the system, volume/velocity data sets recorded in a microfluidic device incorporating multiple channels of 100 μm length and individual widths ranging between 3.0 and 4.0 μm are presented.

CC Cytology - Human 02508
Biophysics - Methods and techniques 10504
Movement 12100
Cardiovascular system - General and methods 14501
Cardiovascular system - Physiology and biochemistry 14504
Blood - General and methods 15001
Blood - Blood and lymph studies 15002
Blood - Blood cell studies 15004

IT Major Concepts
Blood and Lymphatics (Transport and Circulation); Cardiovascular System (Transport and Circulation); Cell Biology; Methods and Techniques

IT Miscellaneous Descriptors
ANALYTICAL METHOD; BLOOD; BLOOD AND LYMPHATICS; BLOOD CAPILLARIES; CARDIOVASCULAR SYSTEM; CIRCULATORY SYSTEM; EQUIPMENT; ERYTHROCYTE FLOW BEHAVIOR; ERYTHROCYTE FLOW VELOCITY PROFILE; ERYTHROCYTE VOLUME; ERYTHROCYTES; IMAGING METHOD; METHODOLOGY; MICROCHANNELS; MICROENGINEERING TECHNOLOGY; MICROFLUIDIC DEVICE; MICRORHEOLOGY; NOVEL INSTRUMENT; PRECISION; REAL-TIME IMAGE PROCESSING

ORGN Classifier
Hominidae 86215
Super Taxa
Primates; Mammalia; Vertebrata; Chordata; Animalia
Organism Name
human
Taxa Notes
Animals, Chordates, Humans, Mammals, Primates, Vertebrates

ANSWER 1 OF 8 BIOSIS COPYRIGHT (c) 2007 The Thomson Corporation on STN

AN 1997:341070 BIOSIS

DN PREV199799640273

TI A novel instrument for studying the flow behaviour of erythrocytes through microchannels simulating human blood capillaries.

AU Sutton, N. [Reprint author]; Tracey, M. C.; Johnston, I. D.; Greenaway, R. S.; Rampling, M. W. [Reprint author]

CS Dep. Physiol. Biophys., Imperial Coll. Sch. Med., St. Mary's, London W2 1PG, UK

SO Microvascular Research, (1997) Vol. 53, No. 3, pp. 272-281.
CODEN: MIVRA6. ISSN: 0026-2862.

DT Article

LA English

ED Entered STN: 11 Aug 1997
Last Updated on STN: 11 Aug 1997

AB A novel instrument has been developed to study the microrheology of erythrocytes as they flow through channels of dimensions similar to human blood capillaries. The channels are produced in silicon substrates using microengineering technology. Accurately defined, physiological driving pressures and temperatures are employed whilst precise, real-time image processing allows individual cells to be monitored continuously during their transit. The instrument characterises each cell in a sample of ca. 1000 in terms of its volume and flow velocity profile during its transit through a channel. The unique representation of the data in volume/velocity space provides new insights into the microrheological behaviour of blood. The image processing and subsequent data analysis enable the system to reject anomalous events such as multiple cell transits, thereby ensuring integrity of the resulting data. By employing an array of microfluidic flow channels we can integrate a number of different but precise and highly reproducible channel sizes and geometries within one array, thereby allowing multiple, concurrent, isobaric measurements on one sample. As an illustration of the performance of the system, volume/velocity data sets recorded in a microfluidic device incorporating multiple channels of 100 μm length and individual widths ranging between 3.0 and 4.0 μm are presented.

CC Cytology - Human 02508
Biophysics - Methods and techniques 10504
Movement 12100
Cardiovascular system - General and methods 14501
Cardiovascular system - Physiology and biochemistry 14504
Blood - General and methods 15001
Blood - Blood and lymph studies 15002
Blood - Blood cell studies 15004

IT Major Concepts
Blood and Lymphatics (Transport and Circulation); Cardiovascular System (Transport and Circulation); Cell Biology; Methods and Techniques

IT Miscellaneous Descriptors
ANALYTICAL METHOD; BLOOD; BLOOD AND LYMPHATICS; BLOOD CAPILLARIES; CARDIOVASCULAR SYSTEM; CIRCULATORY SYSTEM; EQUIPMENT; ERYTHROCYTE FLOW BEHAVIOR; ERYTHROCYTE FLOW VELOCITY PROFILE; ERYTHROCYTE VOLUME; ERYTHROCYTES; IMAGING METHOD; METHODOLOGY; MICROCHANNELS; MICROENGINEERING TECHNOLOGY; MICROFLUIDIC DEVICE; MICRORHEOLOGY; NOVEL INSTRUMENT; PRECISION; REAL-TIME IMAGE PROCESSING

ORGN Classifier
Hominidae 86215
Super Taxa
Primates; Mammalia; Vertebrata; Chordata; Animalia
Organism Name
human
Taxa Notes
Animals, Chordates, Humans, Mammals, Primates, Vertebrates

AN 1999:61773 CAPLUS

DN 130:264301

ED Entered STN: 01 Feb 1999

TI Cell Separation on Microfabricated Electrodes Using
Dielectrophoretic/Gravitational Field-Flow Fractionation

AU Yang, Jun; Huang, Ying; Wang, Xiao-Bo; Becker, Frederick F.; Gascoyne,
Peter R. C.

CS Department of Molecular Pathology, The University of Texas M. D. Anderson
Cancer Center, Houston, TX, 77030, USA

SO Analytical Chemistry (1999), 71(5), 911-918

CODEN: ANCHAM; ISSN: 0003-2700

PB American Chemical Society

DT Journal

LA English

CC 9-7 (Biochemical Methods)

Section cross-reference(s): 6, 13, 76

AB Dielectrophoretic/gravitational field-flow fractionation (DEP/G-FFF) was
used to sep. cultured human breast cancer MDA-435 cells from normal blood
cells mixed together in a sucrose/dextrose medium. An array of
microfabricated, interdigitated electrodes of 50 μm widths and
spacings, and lining the bottom surface of a thin chamber (0.42 mm H .
times. 25 mm W .times. 300 mm L), was used to generate
DEP forces that levitated the cells. A 10- μL cell mixture sample containing
.apprx.50,000 cells was introduced into the chamber, and cancerous and
normal blood cells were levitated to different heights according to the
balance of DEP and gravitational forces. The cells at different heights
were transported at different velocities under the influence of
a parabolic flow profile that was established in the chamber and were
thereby separated Separation performance depended on the frequency and
voltage of

the applied DEP field and the fluid-flow rate. It took as little as 5 min
to achieve cell separation An anal. of the DEP/G-FFF results revealed that the
separation exploited the difference in dielec. and d. properties between cell
populations. The DEP/G-FFF technique is potentially applicable to many
biol. and biomedical problems, especially those related to microfluidic
systems.

ST dielectrophoretic gravitational field flow fractionation cell sepn

IT Animal cell line

(MDA-435; cell separation on microfabricated electrodes using
dielectrophoretic-gravitational field-flow fractionation)

IT Animal cell

Erythrocyte

(cell separation on microfabricated electrodes using dielectrophoretic-
gravitational field-flow fractionation)

IT Electrophoresis apparatus

Separation

(dielectrophoretic/gravitational field-flow fractionation; cell separation
on microfabricated electrodes using dielectrophoretic-gravitational
field-flow fractionation)

IT Dielectrophoresis

(gravitational field-flow fractionation; cell separation on microfabricated
electrodes using dielectrophoretic-gravitational field-flow
fractionation)

RE.CNT 47 THERE ARE 47 CITED REFERENCES AVAILABLE FOR THIS RECORD

RE

(1) Becker, F; J Phys D: Appl Phys 1994, V27, P2659 CAPLUS

(2) Becker, F; Proc Natl Acad Sci U S A 1995, V92, P860 CAPLUS

(3) Cailleau, R; In Vitro 1978, V14, P911 MEDLINE

(4) Caldwell, K; Anal Chem 1993, V65, P1764 CAPLUS

(5) Cheng, J; Nature Biotech 1998, V16, P541 CAPLUS

(6) Fiedler, S; Anal Chem 1998, V70, P1909 CAPLUS

(7) Fuhr, G; Electrical Manipulation of Cells 1996, P37

(8) Fuhr, G; Electromanipulation of cells 1996, P259

ANSWER 4 OF 8 CAPLUS COPYRIGHT 2007 ACS on STN

AN 1999:61773 CAPLUS

DN 130:264301

ED Entered STN: 01 Feb 1999

TI Cell Separation on Microfabricated Electrodes Using
Dielectrophoretic/Gravitational Field-Flow Fractionation

AU Yang, Jun; Huang, Ying; Wang, Xiao-Bo; Becker, Frederick F.; Gascoyne,
Peter R. C.

CS Department of Molecular Pathology, The University of Texas M. D. Anderson
Cancer Center, Houston, TX, 77030, USA

SO Analytical Chemistry (1999), 71(5), 911-918
CODEN: ANCHAM; ISSN: 0003-2700

PB American Chemical Society

DT Journal

LA English

CC 9-7 (Biochemical Methods)

Section cross-reference(s): 6, 13, 76

AB Dielectrophoretic/gravitational field-flow fractionation (DEP/G-FFF) was
used to sep. cultured human breast cancer MDA-435 cells from normal blood
cells mixed together in a sucrose/dextrose medium. An array of
microfabricated, interdigitated electrodes of 50 μm widths and
spacings, and lining the bottom surface of a thin chamber (0.42 mm H .
times. 25 mm W .times. 300 mm L), was used to generate
DEP forces that levitated the cells. A 10- μL cell mixture sample containing
.apprx.50,000 cells was introduced into the chamber, and cancerous and
normal blood cells were levitated to different heights according to the
balance of DEP and gravitational forces. The cells at different heights
were transported at different velocities under the influence of
a parabolic flow profile that was established in the chamber and were
thereby separated Separation performance depended on the frequency and
voltage of

the applied DEP field and the fluid-flow rate. It took as little as 5 min
to achieve cell separation An anal. of the DEP/G-FFF results revealed that the
separation exploited the difference in dielec. and d. properties between cell
populations. The DEP/G-FFF technique is potentially applicable to many
biol. and biomedical problems, especially those related to microfluidic
systems.

ST dielectrophoretic gravitational field flow fractionation cell sepn

IT Animal cell line

(MDA-435; cell separation on microfabricated electrodes using
dielectrophoretic-gravitational field-flow fractionation)

IT Animal cell

Erythrocyte

(cell separation on microfabricated electrodes using dielectrophoretic-
gravitational field-flow fractionation)

IT Electrophoresis apparatus

Separation

(dielectrophoretic/gravitational field-flow fractionation; cell separation
on microfabricated electrodes using dielectrophoretic-gravitational
field-flow fractionation)

IT Dielectrophoresis

(gravitational field-flow fractionation; cell separation on microfabricated
electrodes using dielectrophoretic-gravitational field-flow
fractionation)

RE.CNT 47 THERE ARE 47 CITED REFERENCES AVAILABLE FOR THIS RECORD

RE

(1) Becker, F; J Phys D: Appl Phys 1994, V27, P2659 CAPLUS

(2) Becker, F; Proc Natl Acad Sci U S A 1995, V92, P860 CAPLUS

(3) Cailleau, R; In Vitro 1978, V14, P911 MEDLINE

(4) Caldwell, K; Anal Chem 1993, V65, P1764 CAPLUS

(5) Cheng, J; Nature Biotech 1998, V16, P541 CAPLUS

(6) Fiedler, S; Anal Chem 1998, V70, P1909 CAPLUS

(7) Fuhr, G; Electrical Manipulation of Cells 1996, P37

(8) Fuhr, G; Electromanipulation of cells 1996, P259

- (9) Gascoyne, P; Biophys J 1996, V70, PA330
- (10) Gascoyne, P; IEEE Trans Ind Appl Soc 1997, V33, P670
- (11) Gascoyne, P; Meas Sci Technol 1992, V3, P439
- (12) Giddings, J; Anal Chem 1987, V59, P1957 CAPLUS
- (13) Giddings, J; Science 1993, V60, P1456
- (14) Huang, Y; Biochim Biophys Acta 1996, V1282, P76 CAPLUS
- (15) Huang, Y; Biophys J 1997, V73, P1118 CAPLUS
- (16) Huang, Y; Phys Med Biol 1992, V37, P1499 MEDLINE
- (17) Irimajiri, A; J Theor Biol 1979, V78, P251 MEDLINE
- (18) Jones, T; Electromechanics of Particles 1995
- (19) Kakutani, T; Bioelectrochem Bioenerg 1993, V31, P131
- (20) Kaler, K; Biophys J 1990, V57, P173 MEDLINE
- (21) Kaler, K; J Colloid Interface Sci 1995, V175, P108 CAPLUS
- (22) Kononenko, V; J Chromatogr 1990, V520, P271 CAPLUS
- (23) Lee, S; Anal Chem 1989, V61, P2439 CAPLUS
- (24) Liu, F; Anal Chem 1991, V63, P2115
- (25) Markx, G; Biotech Bioeng 1995, V45, P337 CAPLUS
- (26) Markx, G; J Liq Chromatogr Relat Technol 1997, V20, P2857 CAPLUS
- (27) Markx, G; Microbiology 1994, V140, P585
- (28) Meyers, M; J Microcolumn Sep 1997, V9, P151
- (29) Ormerod, M; Flow Cytometry: A Practical Approach 1994
- (30) Paul, R; J Phys Chem 1993, V97, P4745
- (31) Pazourek, J; J Chromatogr 1995, V715, P259 CAPLUS
- (32) Pethig, R; J Phys D: Appl Phys 1992, V24, P881
- (33) Pethig, R; Phys Med Biol 1987, V32, P933 CAPLUS
- (34) Ratanathanawongs, S; Anal Chem 1992, V64, P6 CAPLUS
- (35) Schwan, H; Ann Biomed Eng 1992, V20, P269 MEDLINE
- (36) Smeland, E; Leukemia 1992, V6, P845 MEDLINE
- (37) Stephens, M; Bone Marrow Transplant 1996, V18, P777 MEDLINE
- (38) Stratton, J; Electrodynamics Theory 1941, P207
- (39) van Den Berg, A; Microsystem Technology in Chemistry and Life Science 1998, P21 CAPLUS
- (40) Wang, X; Biochim Biophys Acta 1995, V1243, P185 CAPLUS
- (41) Wang, X; Biophys J 1998, V74, P2689 CAPLUS
- (42) Wang, X; J Phys D: Appl Phys 1993, V26, P1278 CAPLUS
- (43) Wilding, P; Anal Biochem 1998, V257, P95 CAPLUS
- (44) Williams, P; Chem Eng Commun 1992, V111, P121 CAPLUS
- (45) Williams, P; Chem Eng Commun 1992, V111, P121 CAPLUS
- (46) Williams, P; Colloids Surf 1996, V113, P215 CAPLUS
- (47) Zhang, R; Invasion Metastasis 1991, V11, P204 MEDLINE

- (9) Gascoyne, P; Biophys J 1996, V70, PA330
- (10) Gascoyne, P; IEEE Trans Ind Appl Soc 1997, V33, P670
- (11) Gascoyne, P; Meas Sci Technol 1992, V3, P439
- (12) Giddings, J; Anal Chem 1987, V59, P1957 CAPLUS
- (13) Giddings, J; Science 1993, V60, P1456
- (14) Huang, Y; Biochim Biophys Acta 1996, V1282, P76 CAPLUS
- (15) Huang, Y; Biophys J 1997, V73, P1118 CAPLUS
- (16) Huang, Y; Phys Med Biol 1992, V37, P1499 MEDLINE
- (17) Irimajiri, A; J Theor Biol 1979, V78, P251 MEDLINE
- (18) Jones, T; Electromechanics of Particles 1995
- (19) Kakutani, T; Bioelectrochem Bioenerg 1993, V31, P131
- (20) Kaler, K; Biophys J 1990, V57, P173 MEDLINE
- (21) Kaler, K; J Colloid Interface Sci 1995, V175, P108 CAPLUS
- (22) Kononenko, V; J Chromatogr 1990, V520, P271 CAPLUS
- (23) Lee, S; Anal Chem 1989, V61, P2439 CAPLUS
- (24) Liu, F; Anal Chem 1991, V63, P2115
- (25) Markx, G; Biotech Bioeng 1995, V45, P337 CAPLUS
- (26) Markx, G; J Liq Chromatogr Relat Technol 1997, V20, P2857 CAPLUS
- (27) Markx, G; Microbiology 1994, V140, P585
- (28) Meyers, M; J Microcolumn Sep 1997, V9, P151
- (29) Ormerod, M; Flow Cytometry: A Practical Approach 1994
- (30) Paul, R; J Phys Chem 1993, V97, P4745
- (31) Pazourek, J; J Chromatogr 1995, V715, P259 CAPLUS
- (32) Pethig, R; J Phys D: Appl Phys 1992, V24, P881
- (33) Pethig, R; Phys Med Biol 1987, V32, P933 CAPLUS
- (34) Ratanathanawongs, S; Anal Chem 1992, V64, P6 CAPLUS
- (35) Schwan, H; Ann Biomed Eng 1992, V20, P269 MEDLINE
- (36) Smeland, E; Leukemia 1992, V6, P845 MEDLINE
- (37) Stephens, M; Bone Marrow Transplant 1996, V18, P777 MEDLINE
- (38) Stratton, J; Electrodynamics Theory 1941, P207
- (39) van Den Berg, A; Microsystem Technology in Chemistry and Life Science 1998, P21 CAPLUS
- (40) Wang, X; Biochim Biophys Acta 1995, V1243, P185 CAPLUS
- (41) Wang, X; Biophys J 1998, V74, P2689 CAPLUS
- (42) Wang, X; J Phys D: Appl Phys 1993, V26, P1278 CAPLUS
- (43) Wilding, P; Anal Biochem 1998, V257, P95 CAPLUS
- (44) Williams, P; Chem Eng Commun 1992, V111, P121 CAPLUS
- (45) Williams, P; Chem Eng Commun 1992, V111, P121 CAPLUS
- (46) Williams, P; Colloids Surf 1996, V113, P215 CAPLUS
- (47) Zhang, R; Invasion Metastasis 1991, V11, P204 MEDLINE

AN 1998:676061 CAPLUS
 DN 129:332732
 ED Entered STN: 27 Oct 1998
 TI A particle image velocimetry system for microfluidics
 AU Santiago, J. G.; Wereley, S. T.; Meinhart, C. D.; Beebe, D. J.; Adrian, R. J.
 CS Department of Electrical and Computer Engineering, University of Illinois, Urbana, IL, 61801, USA
 SO Experiments in Fluids (1998), 25(4), 316-319
 CODEN: EXFLDU; ISSN: 0723-4864
 PB Springer-Verlag
 DT Journal
 LA English
 CC 48-7 (Unit Operations and Processes)
 Section cross-reference(s): 73
 AB A micron-resolution particle image velocimetry (micro-PIV) system has been developed to measure instantaneous and ensemble-averaged flow fields in micron-scale fluidic devices. The system utilizes an epifluorescent microscope, 100-300 nm diameter seed particles, and an intensified CCD camera to record high-resolution particle-image fields. Velocity vector fields can be measured with spatial resolsns. down to 6.9 .times. 6.9 .times. 1.5 μm . The vector fields are analyzed using a double-frame cross-correlation algorithm. In this technique, the spatial resolution and the accuracy of the velocity measurements is limited by the diffraction limit of the recording optics, noise in the particle image field, and the interaction of the fluid with the finite-sized seed particles. The stochastic influence of Brownian motion plays a significant role in the accuracy of instantaneous velocity measurements. The micro-PIV technique is applied to measure velocities in a Hele-Shaw flow around a 30 μm (major diameter) elliptical cylinder, with a bulk velocity of approx. 50 $\mu\text{m/s}$.
 ST particle image velocimetry microfluidics
 IT Flow
 (Hele-Shaw; particle image velocimetry system for microfluidics)
 IT Microscopes
 (epifluorescent; particle image velocimetry system for microfluidics)
 IT Imaging
 (fluorescent; particle image velocimetry system for microfluidics)
 IT Micromachines
 (microelectromech. systems; particle image velocimetry system for microfluidics)
 IT Brownian motion
 Fluid dynamics
 Velocity
 (particle image velocimetry system for microfluidics)

RE.CNT 10 THERE ARE 10 CITED REFERENCES AVAILABLE FOR THIS RECORD
 RE

- (1) Adrian, R; Ann Rev Fluid Mech 1991, V23, P261
- (2) Batchelor, G; An introduction to fluid dynamics 1987
- (3) Born, M; Principles of Optics 1991
- (4) Brody, J; Biophys J 1996, V71, P3430 CAPLUS
- (5) Chen, Z; Opt Lett 1997, V22, P64
- (6) Einstein, A; Theory of the Brownian Movement 1905, P1
- (7) Gravesen, P; J Micromech Microeng 1993, P3
- (8) Keane, R; Meas Sci Tech 1995, V6, P754 CAPLUS
- (9) Lanzillotto, A; AIAA Paper 97-1790, 28th Fluid Dynamics Conf 1997
- (10) Prasad, A; Exp Fluids 1992, V13, P105 CAPLUS

AN 1998:676061 CAPLUS
 DN 129:332732
 ED Entered STN: 27 Oct 1998
 TI A particle image velocimetry system for microfluidics
 AU Santiago, J. G.; Wereley, S. T.; Meinhart, C. D.; Beebe, D. J.; Adrian, R. J.
 CS Department of Electrical and Computer Engineering, University of Illinois, Urbana, IL, 61801, USA
 SO Experiments in Fluids (1998), 25(4), 316-319
 CODEN: EXFLDU; ISSN: 0723-4864
 PB Springer-Verlag
 DT Journal
 LA English
 CC 48-7 (Unit Operations and Processes)
 Section cross-reference(s): 73
 AB A micron-resolution particle image velocimetry (micro-PIV) system has been developed to measure instantaneous and ensemble-averaged flow fields in micron-scale fluidic devices. The system utilizes an epifluorescent microscope, 100-300 nm diameter seed particles, and an intensified CCD camera to record high-resolution particle-image fields. Velocity vector fields can be measured with spatial resolsns. down to 6.9 .times. 6.9 .times. 1.5 μm . The vector fields are analyzed using a double-frame cross-correlation algorithm. In this technique, the spatial resolution and the accuracy of the velocity measurements is limited by the diffraction limit of the recording optics, noise in the particle image field, and the interaction of the fluid with the finite-sized seed particles. The stochastic influence of Brownian motion plays a significant role in the accuracy of instantaneous velocity measurements. The micro-PIV technique is applied to measure velocities in a Hele-Shaw flow around a 30 μm (major diameter) elliptical cylinder, with a bulk velocity of approx. 50 $\mu\text{m/s}$.
 ST particle image velocimetry microfluidics
 IT Flow
 (Hele-Shaw; particle image velocimetry system for microfluidics)
 IT Microscopes
 (epifluorescent; particle image velocimetry system for microfluidics)
 IT Imaging
 (fluorescent; particle image velocimetry system for microfluidics)
 IT Micromachines
 (microelectromech. systems; particle image velocimetry system for microfluidics)
 IT Brownian motion
 Fluid dynamics
 Velocity
 (particle image velocimetry system for microfluidics)

RE.CNT 10 THERE ARE 10 CITED REFERENCES AVAILABLE FOR THIS RECORD
 RE

- (1) Adrian, R; Ann Rev Fluid Mech 1991, V23, P261
- (2) Batchelor, G; An introduction to fluid dynamics 1987
- (3) Born, M; Principles of Optics 1991
- (4) Brody, J; Biophys J 1996, V71, P3430 CAPLUS
- (5) Chen, Z; Opt Lett 1997, V22, P64
- (6) Einstein, A; Theory of the Brownian Movement 1905, P1
- (7) Gravesen, P; J Microeng Microeng 1993, P3
- (8) Keane, R; Meas Sci Tech 1995, V6, P754 CAPLUS
- (9) Lanzillotto, A; AIAA Paper 97-1790, 28th Fluid Dynamics Conf 1997
- (10) Prasad, A; Exp Fluids 1992, V13, P105 CAPLUS

ANSWER 6 OF 8 CAPLUS COPYRIGHT 2007 ACS on STN

AN 1997:186940 CAPLUS
DN 126:209094
ED Entered STN: 21 Mar 1997
TI Transport, Manipulation, and Reaction of Biological Cells On-Chip Using Electrokinetic Effects
AU Li, P. C. H.; Harrison, D. J.
CS Department of Chemistry, University of Alberta, Edmonton, AB, T6G 2G2, Can.
SO Analytical Chemistry (1997), 69(8), 1564-1568
CODEN: ANCHAM; ISSN: 0003-2700
PB American Chemical Society
DT Journal
LA English
CC 9-1 (Biochemical Methods)
Section cross-reference(s): 16
AB A microfluidic system was fabricated on a glass chip to study mobilization of biol. cells on-chip. Electroosmotic and/or electrophoretic pumping were used to drive the cell transport within a network of capillary channels. Whole cells such as *Saccharomyces cerevisiae*, canine erythrocyte, and *Escherichia coli* were employed in this work. Photographs are presented to illustrate how cells are selected and transported from one location to another within the capillary network, with velocities up to about 0.5 mm/s in capillaries with a 15- . times. 55- μ m cross-section. The mixing of canine erythrocytes with the lysing agent SDS at an intersection within the chip was performed to demonstrate that cell selection and subsequent reaction can be accomplished within the microchip.
ST cell transport manipulation reaction microfluidic system; glass chip microfluidic system cell reaction; SDS lysis cell microfluidic system
IT Capillary tubes
Cell
Electrokinetic phenomena
Electroosmosis
Electrophoresis
Erythrocyte
Escherichia coli
Saccharomyces cerevisiae
(transport and manipulation and reaction of biol. cells on-chip using electrokinetic effects)
IT Glass, uses
RL: NUU (Other use, unclassified); USES (Uses)
(transport and manipulation and reaction of biol. cells on-chip using electrokinetic effects)
IT 151-21-3, SDS, uses
RL: NUU (Other use, unclassified); USES (Uses)
(transport and manipulation and reaction of biol. cells on-chip using electrokinetic effects)
RE.CNT 31 THERE ARE 31 CITED REFERENCES AVAILABLE FOR THIS RECORD
RE
(1) Agar, N; Red Blood Cells of Domestic Mammals 1983
(2) Berry, D; The Biology of Yeast 1982
(3) Crowley, J; Biophys J 1973, V13, P711 CAPLUS
(4) Dower, W; Nucleic Acids Res 1988, V16, P6127 CAPLUS
(5) Effenhauser, C; Anal Chem 1993, V65, P2637 CAPLUS
(6) Ewing, A; Anal Chem 1994, V66, P527A CAPLUS
(7) Fan, Z; Anal Chem 1994, V66, P177 CAPLUS
(8) Greenwalt, T; The human red cell in vivo 1973
(9) Harrison, D; Anal Chem 1992, V64, P1926 CAPLUS
(10) Harrison, D; Science 1993, V261, P895 CAPLUS
(11) Harrison, D; Technical Digest, Transducers 95, 8th International Conference on Solid-State Sensors and Actuators 1995, P752
(12) Jacobson, S; Anal Chem 1994, V66, P2369 CAPLUS

ANSWER 6 OF 8 CAPLUS COPYRIGHT 2007 ACS on STN

AN 1997:186940 CAPLUS
DN 126:209094
ED Entered STN: 21 Mar 1997
TI Transport, Manipulation, and Reaction of Biological Cells On-Chip Using Electrokinetic Effects
AU Li, P. C. H.; Harrison, D. J.
CS Department of Chemistry, University of Alberta, Edmonton, AB, T6G 2G2, Can.
SO Analytical Chemistry (1997), 69(8), 1564-1568
CODEN: ANCHAM; ISSN: 0003-2700
PB American Chemical Society
DT Journal
LA English
CC 9-1 (Biochemical Methods)
Section cross-reference(s): 16
AB A microfluidic system was fabricated on a glass chip to study mobilization of biol. cells on-chip. Electroosmotic and/or electrophoretic pumping were used to drive the cell transport within a network of capillary channels. Whole cells such as *Saccharomyces cerevisiae*, canine erythrocyte, and *Escherichia coli* were employed in this work. Photographs are presented to illustrate how cells are selected and transported from one location to another within the capillary network, with velocities up to about 0.5 mm/s in capillaries with a 15- . times. 55- μ m cross-section. The mixing of canine erythrocytes with the lysing agent SDS at an intersection within the chip was performed to demonstrate that cell selection and subsequent reaction can be accomplished within the microchip.
ST cell transport manipulation reaction microfluidic system; glass chip microfluidic system cell reaction; SDS lysis cell microfluidic system
IT Capillary tubes
Cell
Electrokinetic phenomena
Electroosmosis
Electrophoresis
Erythrocyte
Escherichia coli
Saccharomyces cerevisiae
(transport and manipulation and reaction of biol. cells on-chip using electrokinetic effects)
IT Glass, uses
RL: NUU (Other use, unclassified); USES (Uses)
(transport and manipulation and reaction of biol. cells on-chip using electrokinetic effects)
IT 151-21-3, SDS, uses
RL: NUU (Other use, unclassified); USES (Uses)
(transport and manipulation and reaction of biol. cells on-chip using electrokinetic effects)

RE.CNT 31 THERE ARE 31 CITED REFERENCES AVAILABLE FOR THIS RECORD

RE

- (1) Agar, N; Red Blood Cells of Domestic Mammals 1983
- (2) Berry, D; The Biology of Yeast 1982
- (3) Crowley, J; Biophys J 1973, V13, P711 CAPLUS
- (4) Dower, W; Nucleic Acids Res 1988, V16, P6127 CAPLUS
- (5) Effenhauser, C; Anal Chem 1993, V65, P2637 CAPLUS
- (6) Ewing, A; Anal Chem 1994, V66, P527A CAPLUS
- (7) Fan, Z; Anal Chem 1994, V66, P177 CAPLUS
- (8) Greenwalt, T; The human red cell in vivo 1973
- (9) Harrison, D; Anal Chem 1992, V64, P1926 CAPLUS
- (10) Harrison, D; Science 1993, V261, P895 CAPLUS
- (11) Harrison, D; Technical Digest, Transducers 95, 8th International Conference on Solid-State Sensors and Actuators 1995, P752
- (12) Jacobson, S; Anal Chem 1994, V66, P2369 CAPLUS

- (13) Jacobson, S; Anal Chem 1994, V66, P3472 CAPLUS
- (14) Jandl, J; Blood-Textbook of Hematology 1987
- (15) Kitagawa, S; Electrophoresis 1995, V16, P1364 CAPLUS
- (16) Kricka, L; Clin Chem 1993, V39, P1944 MEDLINE
- (17) Lehninger, A; Biochemistry, 2nd ed 1975
- (18) Lillard, S; J Chromatogr A 1995, V718, P397 CAPLUS
- (19) Raymond, D; Technical Digest, Transducers 95, 8th International Conference on Solid-State Sensors and Actuators 1995, P760
- (20) Rech, E; Nucleic Acids Res 1990, V18, P1313 CAPLUS
- (21) Seiler, K; Anal Chem 1993, V65, P1481 CAPLUS
- (22) Seiler, K; Anal Chem 1994, V66, P3485 CAPLUS
- (23) Serpersu, E; Biochim Biophys Acta 1985, V812, P779 CAPLUS
- (24) Slappendel, R; Blood 1994, V84, P904 MEDLINE
- (25) Tracey, M; IEEE Trans Biomed Eng 1995, V42, P751 MEDLINE
- (26) Wallenford, R; Anal Chem 1988, V60, P1977
- (27) Washizu, M; Integrated Micro-motion systems-Micromachining, Control and Applications 1990, P417
- (28) Wilding, P; Clin Chem 1994, V40, P43 MEDLINE
- (29) Xue, Q; Anal Chem 1994, V66, P1175 CAPLUS
- (30) Zhu, A; J Chromatogr A 1989, V470, P251 MEDLINE
- (31) Zimmermann, U; Biophys J 1974, V14, P881 MEDLINE

- (13) Jacobson, S; Anal Chem 1994, V66, P3472 CAPLUS
- (14) Jandl, J; Blood-Textbook of Hematology 1987
- (15) Kitagawa, S; Electrophoresis 1995, V16, P1364 CAPLUS
- (16) Kricka, L; Clin Chem 1993, V39, P1944 MEDLINE
- (17) Lehninger, A; Biochemistry, 2nd ed 1975
- (18) Lillard, S; J Chromatogr A 1995, V718, P397 CAPLUS
- (19) Raymond, D; Technical Digest, Transducers 95, 8th International Conference on Solid-State Sensors and Actuators 1995, P760
- (20) Rech, E; Nucleic Acids Res 1990, V18, P1313 CAPLUS
- (21) Seiler, K; Anal Chem 1993, V65, P1481 CAPLUS
- (22) Seiler, K; Anal Chem 1994, V66, P3485 CAPLUS
- (23) Serpersu, E; Biochim Biophys Acta 1985, V812, P779 CAPLUS
- (24) Slappendel, R; Blood 1994, V84, P904 MEDLINE
- (25) Tracey, M; IEEE Trans Biomed Eng 1995, V42, P751 MEDLINE
- (26) Wallenford, R; Anal Chem 1988, V60, P1977
- (27) Washizu, M; Integrated Micro-motion systems-Micromachining, Control and Applications 1990, P417
- (28) Wilding, P; Clin Chem 1994, V40, P43 MEDLINE
- (29) Xue, Q; Anal Chem 1994, V66, P1175 CAPLUS
- (30) Zhu, A; J Chromatogr A 1989, V470, P251 MEDLINE
- (31) Zimmermann, U; Biophys J 1974, V14, P881 MEDLINE

d his

(FILE 'HOME' ENTERED AT 17:00:52 ON 09 FEB 2007)

FILE 'BIOSIS, CAPLUS, EMBASE, MEDLINE, JAPIO' ENTERED AT 17:01:36 ON 09
FEB 2007

L1 16100 S MICROFLUID?
L2 892 S L1 AND VELOCIT?
L3 310 S L2 AND TIME?
L4 1 S L2 AND PLURALI?
L5 8 S L3 AND PD<2000

=>